

T-35

Every plumbers TEE forming machine



IT'S THE TOOLS

THAT SAY HOW GOOD YOU ARE.

T-35 COLLARING MACHINE

DO IT WITH T-DRILL

CUT COSTS - IMPROVE QUALITY - INCREASE PROFIT.

- Only one brazed joint
- No pipe cutting
- No T-fittings
- TEE ratio variation flexibility
- Less chance for leaks or call-backs
- Minimized inspection cost
- Improved flow characteristics
- No costly T-fitting inventories



T-35

The T-DRILL T-35 is a portable, every plumber's TEE forming machine for copper tubes. Designed for most demanding tube installations.

It will give you a competitive advantage by eliminating costs caused by commercial T-fittings.




	O.D.						
	10 mm 3/8"	12 mm 1/2"	15 mm 5/8"	18 mm 3/4"	22 mm 7/8"	28 mm 1 1/8"	35 mm 1 3/8"
15 mm 5/8"	1.0	1.2	1.2				
18 mm 3/4"	1.0	1.2	1.5	1.2			
22 mm 7/8"	1.0	1.2	1.5	1.5	1.5		
28 mm 1 1/8"	1.0	1.2	1.5	1.5	1.5	1.5	
35 mm 1 3/8"	1.0	1.2	1.5	1.5	1.5	1.5	1.5
42 mm 1 5/8"	1.0	1.2	1.5	1.5	1.5	1.5	2.0
54 mm 2 1/8"	1.0	1.2	1.5	1.5	1.5	1.5	2.0
64 mm 2 1/2"	1.0	1.2	1.5	1.5	1.5	1.5	2.0
76.1 mm 3"	1.0	1.2	1.5	1.5	1.5	1.5	2.0
	5/8" 18 mm 3/4" 22 mm 7/8" 28 mm 1 1/8" 35 mm 1 3/8" 42 mm 1 5/8" 54 mm 2 1/8" 64 mm 2 1/2" 76.1 mm	10 mm 3/8" 15 mm 5/8" 1.0 18 mm 3/4" 1.0 22 mm 7/8" 1.0 28 mm 1.0 35 mm 1.0 42 mm 1.0 54 mm 2 1/8" 1.0 64 mm 2 1/2" 76.1 mm 1.0	10 mm 3/8" 12 mm 3/8" 1/2" 15 mm 1.0 1.2 18 mm 3/4" 1.0 1.2 22 mm 7/8" 1.0 1.2 28 mm 1.0 1.2 35 mm 1.0 1.2 42 mm 1.0 1.2 42 mm 1.0 1.2 54 mm 2 1/8" 1.0 1.2 64 mm 2 1/2" 1.0 1.2	10 mm	10 mm	10 mm 3/8" 12 mm 5/8" 18 mm 7/8" 15 mm 5/8" 1.0 1.2 1.2 18 mm 3/4" 1.0 1.2 1.5 1.5 22 mm 7/8" 1.0 1.2 1.5 1.5 1.5 28 mm 1.0 1.2 1.5 1.5 1.5 28 mm 1.0 1.2 1.5 1.5 1.5 35 mm 1.0 1.2 1.5 1.5 1.5 42 mm 1.0 1.2 1.5 1.5 1.5 42 mm 1.0 1.2 1.5 1.5 1.5 42 mm 1.0 1.2 1.5 1.5 1.5 44 mm 1.0 1.2 1.5 1.5 1.5 54 mm 2 1/8" 1.0 1.2 1.5 1.5 1.5 54 mm 2 1/8" 1.0 1.2 1.5 1.5 1.5	10 mm 12 mm 15 mm 18 mm 22 mm 28 mm 15 mm 1.0 1.2 1.2 18 mm 1.0 1.2 1.5 1.2 22 mm 1.0 1.2 1.5 1.5 22 mm 1.0 1.2 1.5 1.5 28 mm 1.0 1.2 1.5 1.5 1.5 35 mm 1.0 1.2 1.5 1.5 1.5 1.5 42 mm 1.0 1.2 1.5 1.5 1.5 1.5 42 mm 1.0 1.2 1.5 1.5 1.5 1.5 54 mm 1.0 1.2 1.5 1.5 1.5 1.5 64 mm 1.0 1.2 1.5 1.5 1.5 1.5 76.1 mm 1.0 1.2 1.5 1.5 1.5 1.5



T-DRILL PROCESS

1. Pilot hole is drilled 2. Forming pins are extended 3. Collar is formed



MANUFACTURER:

T-DRILL OY

T-DRILL OY P.O. Box 20, FIN-66401 LAIHIA, Finland Tel.+358 6 475 3333 Telefax +358 6 475 3300 e-mail: sales@t-drill.fi www.t-drill.fi T-DRILL Industries Inc.
1740 Corporate Drive, Suite #820,
Norcross, Georgia 30093 USA
Tel. +1-770-925-0520, Toll-free +1-800-554-2730
Telefax +1-770-925-3912
sales@t-drill.com, www.t-drill.com

REPRESENTED BY: